



OUTLET	2	4	6	8
Operating Input Voltage	220-240 VAC 50-60 Hz 110-120 VAC 50-60 Hz 1,5-24 VDC	220-240 VAC 50-60 Hz 110-120 VAC 50-60 Hz 1,5-24 VDC	220-240 VAC 50-60 Hz 110-120 VAC 50-60 Hz 1,5-24 VDC	220-240 VAC 50-60 Hz 110-120 VAC 50-60 Hz 1,5-24 VDC
Spark Frequency	1,5 to 3,5 Hz at 220 VAC 50 Hz 1,5 to 3,5 Hz at 110 VAC 60 Hz 3 to 5 Hz at 12 VDC	1,5 to 3,5 Hz at 220 VAC 50 Hz 1,5 to 3,5 Hz at 110 VAC 60 Hz 3 to 5 Hz at 12 VDC	1,5 to 3,5 Hz at 220 VAC 50 Hz 1,5 to 3,5 Hz at 110 VAC 60 Hz 3 to 5 Hz at 12 VDC	1,5 to 3,5 Hz at 220 VAC 50 Hz 1,5 to 3,5 Hz at 110 VAC 60 Hz 3 to 5 Hz at 12 VDC
Spark Distance Test	Min. 6mm	Min. 6mm	Min. 6mm	Min. 6mm
Spark Voltage	≥ 10KV @ 30pF	≥ 10KV @ 30pF	≥ 10KV @ 30pF	≥ 10KV @ 30pF
Operating Temperature	Max. 120°C	Max. 120°C	Max. 120°C	Max. 120°C
Storage Temperature	-20°C +85°C	-20°C +85°C	-20°C +85°C	-20°C +85°C
Service Life	5.000.000	5.000.000	5.000.000	5.000.000
VDE,AGA,CSA,EMC, ROHS	☑	☑	☑	☑