ONLINE CERTIFICATIONS DIRECTORY

QCRV.E199260
Outlet Bushings and Fittings

Page Bottom

Outlet Bushings and Fittings

See General Information for Outlet Bushings and Fittings

BIMED TEKNIK ALETLER SAN TIC A S E199260
BEYLIKDUZU MEVKII
SS BAKIR VE PIRINC SAN
ORKIDE CD NO 15
34524 ISTANBUL, BEYLIKDUZU TURKEY

Cord connectors, Cat. Nos. BNSPA-01, -21, BNSPB-02, BNSPC-02, -22, BNSPD-03, -23, BSP-04, BSPA-01, BSPB-02, BSPC-02, BSPD-03.

Dry locations flexible cord connectors, Cat. Nos. BM-12, BM-02, BM-22, BM-18, BM-08, BM-28, BM-19, BM-09, BM-29, BM-20, BM-10, BM-30, BSPB-12, BSPG-02, BSPB-22, BS-24, BS-04, BS-14, BS-28, BS-08, BS-18, BS-29, BS-09, BS-19, BS-30, BS-10, BS-20, BM-EN-22, BM-EN-02, BM-EN-12, BM-EN-23, BM-EN-03, BM-EN-13, BM-EN-24, BM-EN-04, BM-EN-14, BM-EN-25, BM-EN-05, BM-EN-15, BMSP-02, BMSP-12, BMSP-22, BSPB-12, BSPG-02, BSPB-22, BNSPB-22, BNSPB-02, BNSPB-12.

Liquid tight flexible cord fittings, Cat. Nos. BSN-04, BSNA-01, BSNC-02, BSND-03.

Cat. Nos. BMEM-E2, BMBC-02, BMSC-02, BNEM-02, BNBC-02, BNSC-02, BMEM-E6, BMBC-E6, BMSC-E6, BMEM-E7, BMBC-07, BMSC-07, BMEM-E3, BMSC-03, BMBC-E3, BMEM-E4, BMSC-04, BMBC-E4, BMEM-E5, BMSC-05, BMBC-E5.

Cat. Nos. BSPC-22, BSPC-02, BSPC-12, BSP-24, BSP-04, BSP-14, BS-25, BS-05, BS-15, BS-27, BS-07, BS-17, BM-23, BM-03, BM-13, BM-25, BM-05, BM-15, BM-27, BM-07, BM-17; Straight Long threads, Cat. Nos. BM-24, BM-04, BM-14; Straight Spiral Necks, Cat. Nos. BNSPC-22, BNSPC-02, BNSPC-12, BNSP-24, BNSP-04, BNSPD-14, BSSP-25, BSSP-05, BSSP-15, BMSP-23, BMSP-03, BMSP-13, BMSP-25, BMSP-05, BMSP-15.

Last Updated on 2010-10-28

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

ONLINE CERTIFICATIONS DIRECTORY

QCRV2.E199260
Outlet Bushings and Fittings - Component

Page Bottom

Outlet Bushings and Fittings - Component

See General Information for Outlet Bushings and Fittings - Component

BIMED TEKNIK ALETLER SAN TIC A S E199260
BEYLIKDUZU MEVKII
SS BAKIR VE PIRINC SAN
ORKIDE CD NO 15
34524 ISTANBUL, BEYLIKDUZU TURKEY

Cord connector-liquid-tight flexible, Cat. Nos. BM01, BM02.

Dry locations flexible cord connectors, Cat. Nos. BM-0S, BM-1S, BM-2S, BM-EN-0S, BM-EN-1S, BM-EN-2S, BM-EN-01, BM-EN-11, BM-EN-21, BM-EN-01S, BM-EN-11S, BM-EN-21S, BMSP-0S, BMSP-1S, BMSP-2S, BS-01, BS-02, BS-11, BS-12, BS-21, BS-22, BSSP-21, BSSP-01, BSSP-11, BSSP-22, BSSP-02, BSSP-12.

Liquid-tight flexible cord fittings, Cat. Nos. BMBC-0S, BMEM-ES, BMSC-0S, BNBC-0S, BNEM-0S, BNSC-0S, BMBC-E1, BMEM-E1, BMSC-01, BNBC-01, BNEM-01, BNSC-01, BMX-22 (2X3).

Straight Cat. Nos. BSPA-21, BSPA-01, BSPA-11, BS-23, BS-03, BS-13, BM-21, BM-01, BM-11; Straight Long threads, Cat. Nos. BM-21L, BM-01L, BM-11L; Straight Spiral Necks, Cat. Nos. BNSPA-21, BNSPA-01, BNSPA-11, BSSP-23, BSSP-03, BSSP-13, BMSP-21, BMSP-01, BMSP-11.

Marking: Company name and catalog designation.
Last Updated on 2010-10-28

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the