






Technical Details		
<b>Material</b>	<b>Body</b>	Brass, Nickel plated
	<b>Cap</b>	Brass, Nickel plated
	<b>Seal</b>	CR (Chloroprene Rubber)
	<b>Clamp.Insert</b>	Polyamide 6
	<b>O-ring</b>	NBR
<b>Flammability</b>	V2 (According to UL 94)	
<b>Protection Class</b>	IP 68 - 5 Bar	
<b>Operating Temperature</b>	<b>Permanent</b>	-20 °C up to +100 °C
	<b>Intermittent</b>	-40 °C up to +150 °C
<b>Attachment Thread</b>	ANSI B 1.20.1	

Benefits	
	Suitable for highest demands of todays technology
	Easy to assemble
	Easy handling
	Water tight
	Strain relief

Accessories	
	Lock nuts
	Reducing seals
	Flat cable seals
	Multihole seals

Approvals	
	VDE, UL, UR, CSA, see page 82

Remarks	
	Different sealing types available
	Large accessory range
	Manufactured according to the requirements of EN 50262

Thread Type	 Clamping Range Ø min-max inch	Technical Information						Codes	Packing Information	
		TL inch	TD inch	 SW1 inch	 SW2 inch	Max. H inch	D inch		 Inner Pack	 Box/Min.OQ
NPT 3/8"	0,157 - 0,314	0,452	0,629	0,787	0,787	0,905	0,866	BNBC-01	50	1,000
NPT 3/8"	0,196 - 0,393	0,452	0,629	0,787	0,787	0,944	0,866	BNBC-01S	50	1,000
NPT 1/2"	0,236 - 0,472	0,511	0,826	0,866	0,866	1,003	0,964	BNBC-02	50	800
NPT 1/2"	0,393 - 0,551	0,511	0,826	0,944	1,062	1,086	1,169	BNBC-02S	50	600
NPT 3/4"	0,511 - 0,708	0,511	1,141	1,181	1,181	1,338	1,299	BNBC-03	25	300
NPT 1"	0,708 - 0,984	0,511	1,259	1,574	1,692	1,692	1,751	BNBC-04	10	160