



Technical Details		
Material	Body	PA 6 (Polyamide 6)
	Cap	PA 6 (Polyamide 6)
	Seal	CR (Chloroprene Rubber)
Flammability		V2 (According to UL 94)
Protection Class		IP 68 - 5 Bar
Operating Temperature	Permanent	-20 °C up to +100 °C
	Intermittent	-30 °C up to +150 °C
	Attachment Thread	ANSI B 1.20.1

Benefits	
	Easy to assemble
	Easy handling

Accessories	
	Lock nuts
	Protection tabs
	Dust plugs
	Reducing seals
	Flat cable seals
	Multihole seals

Approvals	
	VDE, UL, UR, CSA, see page 82
UV Test Report Ref. & Standard	RES 107572 & UL514B § 8.26.7

Remarks	
	Other colours on request (Red-White-Blue)
	Different sealing types available
	Large accessory range
	Manufactured according to the requirements of EN 50262

Thread Type	Technical Information							Codes			Packing Information	
	Clamp. Range Ø min-max mm	Clamp. Range Ø min-max inch	TL inch	TD inch	SW inch	Max. H inch	D inch	Ral 7001	Ral 7035	Ral 9005	Inner Pack	Box/Min.OQ.
NPT 3/8"	5,0 - 10,0	0,197-0,394	0,590	0,653	0,866	1,102	0,984	BSPA-01	BSPA-11	BSPA-21	50	2.000
NPT 1/2"	6,0 - 12,0	0,236-0,472	0,590	0,809	0,945	1,141	1,094	BSPB-02	BSPB-12	BSPB-22	50	1.800
	10,0 - 14,0	0,394-0,551			1,063	1,220	1,212	BSPC-02	BSPC-12	BSPC-22		
NPT 3/4"	13,0 - 18,0	0,511-0,709	0,590	1,020	1,299	1,377	1,488	BSPD-03	BSPD-13	BSPD-23	25	750
NPT 1"	18,0 - 25,0	0,709-0,984	0,709	1,275	1,654	1,574	1,889	BSP-04	BSP-14	BSP-24	20	600
Glands With Reducing Sealing												
NPT 3/8"	3,0 - 7,0	0,118-0,276	0,590	0,653	0,866	1,102	0,984	BSPA-01R	BSPA-11R	BSPA-21R	50	2.000
NPT 1/2"	5,0 - 9,0	0,197-0,354	0,590	0,809	0,945	1,141	1,094	BSPB-02R	BSPB-12R	BSPB-22R	50	1.800
	7,0 - 12,0	0,276-0,472			1,063	1,220	1,212	BSPC-02R	BSPC-12R	BSPC-22R		
NPT 3/4"	9,0 - 16,0	0,354-0,630	0,590	1,020	1,299	1,377	1,488	BSPD-03R	BSPD-13R	BSPD-23R	25	750
NPT 1"	12,0 - 20,0	0,472-0,787	0,709	1,275	1,654	1,574	1,889	BSP-04R	BSP-14R	BSP-24R	20	600