




PA277C

**Cable clamp.
For snap-in fixing on chassis**



TECHNICAL DATA

| | IEC Standards | | | American Standards | | |
|----------------------------------|--|--------------|----------------|--|----------------|----------------|
| | A | B | C | D | E | F |
| Dimensions mm (inches) | 28.5 (1.12) | 26 (1.02) | 37.6 (1.48) | 50.6 (1.99) | 14.5 (0.57) | 3.5 (0.138) |
| Wire size | 3 x 0.75 sqmm ÷ 3 x 1.5 sqmm (max. cable Ø 10 mm) | | | 3 x 20 AWG ÷ 3 x 16 AWG (max. cable Ø 0.4") | | |
| Working Temperature | -5 ÷ 125 °C (short time 155 °C) | | | 23 ÷ 221 °F | | |
| Plastic Material | Polyamide PA6 black colour, UL94-V2, GWT850 °C | | | | | |
| Cable Clamp Screw | 3.5 x 15 mm (0.14" x 0.60") HI-LO | | | | | |

| Approvals | File Nr. | Ratings (sqmm/AWG – V – A – T) | Standard References |
|---|----------|--------------------------------|--|
|  | EN 568 | Gr. 7/10 mm – 125°C | EN 60598-1; /A1; /A12; /A13; EN 60335-1 |

| PACKAGING | | | | |
|-----------|--------|-------|--------------------|-------------|
| Type | P-N | Pack. | Dim. Pack. (LxHxP) | Weight (Kg) |
| PA 277C | 970581 | 2000 | 40x39x40 | 17.5 |

DIMENSIONAL
DRAWING

