




8 (3) A / 250 VAC
T125 °C
EN 61058

8 A / 125 VAC
T65 °C
UL 1054



NOTES
2/3/4 position body

SLIDE SWITCHES **LF**

TYPICAL APPLICATIONS	Cooker hoods, hairdryers
WIRING DIAGRAMS	<ul style="list-style-type: none"> ▶ Single or double-pole switch 2 positions ▶ Double-pole switch 3 positions ▶ Double-pole switch 4 positions
CYCLE NR	10.000
CUT OUT	Rear panel
AMBIENT TEMPERATURE	125 °C
GWFI	850 °C
GWIT	750 °C



10 A / 250 VAC
T85 °C
EN 61058

13 A / 125 VAC
6.5 A / 250 VAC
T55 °C
UL 1054



NOTES
5 position body available

SLIDE SWITCHES **P**

TYPICAL APPLICATIONS	Cooking, small appliances
WIRING DIAGRAMS	<ul style="list-style-type: none"> ▶ Double-pole switch 3 positions ▶ Double-pole switch 4 positions ▶ Double-pole switch 5 positions
CYCLE NR	10.000
CUT OUT	-
AMBIENT TEMPERATURE	120 °C
GWFI	850 °C
GWIT	750 °C on demand



3 VDC 2,5 A - 20 VDC 5 A



NOTES
Designed for direct-current loads

SLIDE SWITCHES **HUS**

TYPICAL APPLICATIONS	Gardening tools
WIRING DIAGRAMS	▶ Single-pole switch
CYCLE NR	-
CUT OUT	27x12 mm
AMBIENT TEMPERATURE	-
GWFI	850 °C
GWIT	750 °C on demand



13 (3) A / 250 VAC
6 (6) A / 250 VAC
T150 °C
EN 61058

13 A / 125 VAC
T65 °C
UL 1054



NOTES
Available shafts up to 26 mm

ROTARY SWITCHES **R1**

TYPICAL APPLICATIONS	Fan heaters, small ovens, cleaners
WIRING DIAGRAMS	▶ Single or double-pole switch up to 6 positions 30° step
CYCLE NR	50.000
CUT OUT	28 mm interaxes screws
AMBIENT TEMPERATURE	150 °C
GWFI	850 °C
GWIT	750 °C on demand