



B4MASK



TYPICAL APPLICATIONS	Outdoor electrical equipments, pumps, high pressure cleaners
FUNCTIONS	<ul style="list-style-type: none"> ■ SPST ■ DPST, illuminated or not ■ DPCO
PROTECTION DEGREE	IP 65
CYCLE No.	50.000
CUT OUT	30x22 mm
AMBIENT TEMPERATURE	120 °C
GWT	850 °C
GWT NO FLAME (<2sec)	750 °C on demand

B 4 M A S K

?

DRAWING

TERMINAL



→ Available in Gloss or Mat

1 Gloss version

3 Mat version


→ Available in Gloss or Mat

4 Gloss version

5 Mat version

L Gloss version

P Mat version



Z	Y	X
0,75 ... 1,25	22,0	$\begin{matrix} +0,2 \\ 0 \end{matrix}$ 30,2 ±0,1
1,25 ... 2,0	22,0	$\begin{matrix} +0,2 \\ 0 \end{matrix}$ 30,6 ±0,1
2,0 ... 3,0	22,0	$\begin{matrix} +0,2 \\ 0 \end{matrix}$ 30,8 ±0,1

TERMINAL	FUNCTION	RATING	RUBBER COLOUR	ROCKER COLOUR	MARKING COLOUR	MARKING
B	4	M	A	S	K	0 0 0

?	?	?	?	?	?	?	0	0	0
---	---	---	---	---	---	---	---	---	---

FUNCTION

1

2

8

9 Terminal 1 - 3

RATING

C

Function 9

16 (6) A / 250 VAC
10 (4) A / 250 VAC - 5E4
T120/55 °C
EN 61058

20 A / 125 VAC
 16 A / 250 VAC
 1/3 HP - 125 VAC
 3/4 HP - 250 VAC
 T105 °C
 UL 1054
 CSA C22.2

E

Function 1

16 (8) A / 250 VAC
12 (10) A / 250 VAC - 5E4
T120 / 55 °C
EN 61058

20 A / 125 VAC
 16 A / 250 VAC
 1/3 HP - 125 VAC
 3/4 HP - 250 VAC
 T105 °C
 UL 1054
 CSA C22.2

N

Function 2 - 8

16 (8) A / 250 VAC
12 (10) A / 250 VAC - 5E4
T120/55 °C
EN 61058

20 A / 125 VAC
 16 A / 250 VAC
 3/4 HP - 125 / 250 VAC
 T105 °C
 UL 1054
 CSA C22.2

S

Function 2 - 8

20 (10) A / 250 VAC
14 (14) A / 250 VAC - 5E4
T120/55 °C
EN 61058

25 A / 125 VAC
 16 A / 250 VAC
 3/4 HP - 125 / 250 VAC
 T105 °C
 UL 1054
 CSA C22.2

RUBBER COLOUR

1 black

ROCKER COLOUR

1 black

2 white

3 orange

ILLUMINATED ✨

G red

E green

L white

F blue

BRIGHT ✨

A orange

V green

X custom

MARKING COLOUR

0 none

1 black

2 white

X custom

MARKING

0

1

A

9

X