


MORSETTIERA 12 POLI IN PA66 PASSO 10MM CON LAMELLA BASE H 4,5MM

V2-V0

PILLAR TERMINAL BLOCK 12 POLES PA66 PITCH 10MM WITH WIRE PROTECTOR RAISED 4,5 MM BASE



DATI TECNICI / TECHNICAL DATA

	IEC STANDARDS	USA
Ratings	450V - 32A	600V - 30A
Wire size	1,0 ÷ 4 mm ²	20 ÷ 12 AWG
Approvals	ENEC File nbr 35-131664 UL/CSA filr nbr.E308822 (See approvals document for additional details) 	
Plastic Material	Polyamide 66, UL94 V2, GWIT 850°C / UL94-V0 GWIT775	
Metal Parts	Cage insert made in nickel plated brass; M3 (0.5Nm) Captive screw made in zinc plated steel. Stainless steel spring wire protector.	

COD.	DESCRIZIONE /DESCRIPTION	IP	MATERIAL	Ta IEC (°C)	Ta UL (°C°F)	GWT (°C)	PACKAGING
3MR10WN12NY-32-KR	MORS. TYPE T06-H12W(A) WN NY 12 POLI	00	POLYAMIDE UL94-V2	110	105/221	850	500
3MR10WN12HTGWT-32-KR	MORS. TYPE T06-H12W(V0) WN GWT 12 POLI	00	POLYAMIDE UL94-V0	135	105/221	750	500

DISEGNO TECNICO / TECHNICAL DRAW

