


# MORSETTIERA 12 POLI IN PA66 PASSO 12MM CON LAMELLA

PILLAR TERMINAL BLOCK 12 POLES PA66 PITCH 12MM WITH WIRE PROTECTOR

**V2-V0**


## DATI TECNICI / TECHNICAL DATA

	IEC STANDARDS	USA
<b>Ratings</b>	450V - 57A	600V - 35A
<b>Wire size</b>	4,0 ÷ 10,0 mm <sup>2</sup>	20 ÷ 10 AWG
<b>Approvals</b>	ENEC File nbr 35-131664 UL/CSA filr nbr.E308822 (See approvals document for additional details) 	
<b>Plastic Material</b>	Polyamide 66, UL94 V2, GWIT 850°C / UL94 V0, GWIT775	
<b>Metal Parts</b>	Cage insert made in nickel plated brass; M3,5 (0.8Nm) Captive screw made in zinc plated steel. Stainless steel spring wire protector.	

COD.	DESCRIZIONE /DESCRIPTION	IP	MATERIAL	Ta IEC (°C)	Ta UL (°C°F)	GWT (°C)	PACKAGING
3MR12WN12NY-KR	MORS. TYPE T10-M12W(A) WN NY 12 POLI	00	POLYAMIDE UL94-V2	110	105/221	850	500
3MR12WN12HTGWT-KR	MORS. TYPE T10-M12W(V0) WN GWT 12 POLI	00	POLYAMIDE UL94-V0	135	105/221	750	500

## DISEGNO TECNICO / TECHNICAL DRAW

