




# MORSETTIERA 12 POLI IN PA66 PASSO 13,5MM CON LAMELLA

PILLAR TERMINAL BLOCK 12 POLES PA66 PITCH 13.5MM WITH WIRE PROTECTOR

**V2-V0**


## DATI TECNICI / TECHNICAL DATA

	IEC STANDARDS	USA
<b>Ratings</b>	500V - 57A	300V - 50A
<b>Wire size</b>	4,0 ÷ 10,0 mm <sup>2</sup>	20 ÷ 8 AWG
<b>Approvals</b>	VDE File nbr 40016431  UL/CSA filr nbr.E152546 (See approvals document for additional details)  	
<b>Plastic Material</b>	Polyamide 66, UL94 V2, GWIT 850°C / UL94 V0, GWT750	
<b>Metal Parts</b>	Cage insert made in nickel plated brass; M4 (1,2Nm) Captive screw made in zinc plated steel. Stainless steel spring wire protector.	

COD.	DESCRIZIONE / DESCRIPTION	IP	MATERIAL	Ta IEC (°C)	Ta UL (°C°F)	GWT (°C)	PACKAGING
3MR14WN12NY	MORS. TYPE PA14 WN NY 12 POLI	00	POLYAMIDE UL94-V2	110	105/221	850	250
3MR14WN12HTGWT	MORS. TYPE PA14 WN GWT 12 POLI	00	POLYAMIDE UL94-V0	140	105/221	750	250

## DISEGNO TECNICO / TECHNICAL DRAW

