



# MORSETTIERA 1-5 POLI CON PORTAFUSIBILE PA66 PASSO 10MM

FUSE HOLDER PILLAR TERMINAL BLOCK 1-5 POLES PA66 PITCH 10MM




## DATI TECNICI / TECHNICAL DATA

	IEC STANDARDS	USA
<b>Ratings</b>	250VAC - 6,3A	300V - 6,3A
<b>Wire size</b>	2.5 mm <sup>2</sup>	22 ÷ 14 AWG
<b>Working Temperat.</b>	-40°C - +105°C	-40 - 221°F
<b>Plastic Material</b>	Polyamide, UL94 V0, GWIT 850°C	
<b>Metal Parts</b>	Cage insert made in nickel plated brass; M3 (0.5Nm) Captive screw made in zinc plated steel	

Approvals	Standard References
<b>VDE</b>	 DIN EN 60998-2-1 (VDE 0613 Teil 2-1):2005-03; EN 60998-2-1:2004 DIN EN 60998-1 (VDE 0613 Teil 1):2005-03; EN 60998-1:2004 (40024802)  DIN EN 60127-1 (VDE0820-1):2011; EN60127-1:2006+A1:2011 DIN EN60127-6 (VDE0820 Teil 6):2003-10; EN60127-6:1994+A1:1996+A2:2003 IEC60127-1 (ed.2) IEC60127-6 (ed.1);am1;am2 (40026310)
<b>UL</b>	UL 1059 (E228872)

## PACKAGING

Type	P-N	Pack.
<b>DG801-01P-11-16AH</b>	3MRDG801-01P-16 anti-rotation lug	1700 pcs
<b>DG801-02P-11-16AH</b>	3MRDG801-02P-16 anti-rotation lug	1000 pcs
<b>DG801-03P-11-16AH</b>	3MRDG801-03P-16 anti-rotation lug	640 pcs
<b>DG801-04P-11-16AH</b>	3MRDG801-04P-16 anti-rotation lug	400 pcs
<b>DG801-05P-11-16AH</b>	3MRDG801-05P-16 anti-rotation lug	420 pcs

**DISEGNO TECNICO / TECHNICAL DRAW**

