



# MORSETTIERA SNAP-IN VITE/FASTON 3 POLI KL130

SCREW TO TAB TERMINAL BLOCK SNAP-IN WITH 3 POLES KL130



## DATI TECNICI / TECHNICAL DATA

	EUROPA	USA
Sezione cavo / Cable section	1,0 ÷ 6,0 mm <sup>2</sup>	18-8 AWG
Tensione nominale / Nominal Voltage	450 V	300 V
Corrente max / Max. Rating	41 A	41 A
Temp. d'esercizio / Working Temperature	T 150°C	T 130°C
Grado di protezione / Protection degree	IP 00	
Corpo isolante / Plastic material	PA66 - GF25% - CLASS V-0 - GWT 750°C	
Numero poli / Number of poles	3	
Coppia di serraggio / Tightening torque	0,5-1,0Nm (Max 2.5Nm)	
Dima di foratura / Cut out	Vedi disegno tecnico / Refer to technical drawing	
Parti metalliche / Metal parts	M6 zinc plated steel screw; 6,3X0,8 zinc plated steel tab insert; zinc plated steel grounding tab; Shunt insert made in copper (where assembled).	

Approvals	Standard References
VDE 	DIN EN 60998-1:2005-03; EN 60998-1:2004; DIN EN 60998-2-1: 2005-03; EN 60998-2-1:2004 DIN EN 61210 2011-06; EN 61210:2010
UL CSA 	1-UL Standard: UL 1059 Standard for terminal blocks Edition 4 Rev.Date 2011-10-14 2-Canadian Standard: CSA C22.2 NO.158-10 terminal blocks Edition 3-Issue Date 2010-03-01

## PACKAGING

Type	Poli / Poles	P-N	Pack.	Peso / Weight	Misure / Size
KL130	3	3MRN07007908	250 pz.	8,11 Kg.	300x400x195mm

**DISEGNO TECNICO / TECHNICAL DRAW**

