



SX17

WIRING DIAGRAMS	<ul style="list-style-type: none"> ▶ Neon or fluorescent lamp ▶ Anti-luminiscence resistor available ▶ LED in A.C. or D.C. version
VOLTAGE	2V, 12V, 24V, 125V, 250V, 400V
TEMPERATURE	From T75 °C to T150 °C according to the version
COLOUR	Red, orange, green, blue, colourless. Other colours available on customer's request
WIRE ENDS AND CONNECTORS	PVC or silicone cables, available pre-stripped wires end 6,5 mm or with clamped connectors
LIGHT SOURCE	LED: available for every voltage Incandescence: 12V - 24V Neon: from 125V



SX21 / SX214

WIRING DIAGRAMS	<ul style="list-style-type: none"> ▶ Neon or fluorescent lamp ▶ Anti-luminiscence resistor available ▶ LED in A.C. or D.C. version
VOLTAGE	2V, 12V, 24V, 125V, 250V, 400V
TEMPERATURE	From T75 °C to T150 °C according to the version
COLOUR	Red, orange, green, blue, colourless. Other colours available on customer's request
WIRE ENDS AND CONNECTORS	PVC or silicone cables, available pre-stripped wires end 6,5 mm or with clamped connectors
LIGHT SOURCE	LED: available for every voltage Incandescence: 12V - 24V Neon: from 125V

LENS 57	LENS 41	LENS 51	LENS 43	LENS 53	LENS 59	SX21T Lenses
HOLE Ø 10 mm	HOLE Ø 12 mm	HOLE Ø 12 mm	HOLE Ø 13 mm	HOLE Ø 13 mm	HOLE Ø 13 mm	

LENS P	LENS Q	SX214 Lenses
HOLE Ø 11,5 mm	HOLE 10,5x7 mm	



HOLE Ø 6 mm

SX24 / SX244

WIRING DIAGRAMS	<ul style="list-style-type: none"> ▶ Neon or fluorescent lamp ▶ Anti-luminiscence resistor available ▶ LED in A.C. or D.C. version
VOLTAGE	2V, 12V, 24V, 125V, 250V, 400V
TEMPERATURE	From T75 °C to T150 °C according to the version
COLOUR	Red, orange, green, blue, colourless. Other colours available on customer's request
WIRE ENDS AND CONNECTORS	PVC or silicone cables, available pre-stripped wires end 6,5 mm or with clamped connectors
LIGHT SOURCE	LED: available for every voltage Incandescence: 12V - 24V Neon: from 125V